

Principal dimensions (mm)			Basic load ratings KN		P _u	Speed ratings rpm		Weight kg	Designation	Dimensions mm				Abutment and fillet dimensions mm			Value
d	D	B	dyc Cr	stc Cor		Speed Ratings	Limiting Speed			d	d ₁ ~	D ₁ ~	r _{1,2} Min	d _a Min	Da Max	r _a Max	
65	120	23	58,5	40,5	1,73	16000	8500	0,92	6213/HC5C3	65	83,3	106	1,5	74	111	1,5	15
70	110	20	39,7	31	1,32	16000	9000	0,57	6014/HC5C3	70	82,9	99,9	1,1	76	104	1	16
70	125	24	63,7	45	1,9	15000	8500	0,99	6214/HC5C3	70	87,1	111	1,5	79	116	1,5	15
75	160	37	119	76,5	3	12000	6700	2,60	6315/HC5C3	75	101	138	2,1	87	148	2	13
80	170	39	130	86,5	3,25	12000	6300	2,80	6316/HC5C3	80	108	147	2,1	92	158	2	13
95	200	45	159	118	4,15	9500	5300	4,90	6319/HC5C3	95	121	172	3	109	186	2,5	13
110	240	50	203	180	5,7	8000	4500	8,15	6322/HC5C3	110	149	205	3	124	226	2,5	13