

Bearing No.	Shaft Dia.		Dimensions							Basicload rating		Mass	
	d		D	B	C	S	S1	G	h	ds	Dynamic Cr	Static Cor	S
	(in.)	(mm)											(kg)
UCX05-14	7/8		62	38.1	19	15.9	22.2	6	5	1/4-28UNF	19500	11200	0.42
UCX05-15	15/16		62	38.1	19	15.9	22.2	6	5	1/4-28UNF	19550	11200	0.4
UCX05		25	62	38.1	19	15.9	22.2	6	5	M6X1	19500	11200	0.39
UCX05-16	1		62	38.1	19	15.9	22.2	6	5	1/4-28UNF	19500	11200	0.38
UCX06-18	1-1/8		72	42.9	20	17.5	25.4	6.5	5.8	5/16-24UNF	25700	15200	0.58
UCX06		30	72	42.9	20	17.5	25.4	6.5	5.8	M8X1	25700	15200	0.58
UCX06-19	1-3/16		72	42.9	20	17.5	25.4	6.5	5.8	5/16-24UNF	25700	15200	0.58
UCX06-20	1-1/4		72	42.9	20	17.5	25.4	6.5	5.8	5/16-24UNF	25700	15200	0.55
UCX07-22	1-3/8		80	49.2	21	19	30.2	8	6.3	5/16-24UNF	29600	18200	0.75
UCX07		35	80	49.2	21	19	30.2	8	6.3	M8X1	29600	18200	0.75
UCX07-23	1-7/16		80	49.2	20	17.5	25.4	6.5	5.8	5/16-24UNF	29600	18200	0.72
UCX08-24	1-1/2		85	49.2	22	19	30.2	8	6.8	5/16-24UNF	31850	20800	0.87
UCX08-25	1-9/16		85	49.2	22	19	30.2	8	6.8	5/16-24UNF	31850	20800	0.87
UCX08		40	85	49.2	22	19	30.2	8	6.8	M8X1	31850	20800	0.83
UCX09-26	1-5/8		90	51.6	23	19	32.6	9	6.5	3/8-24UHF	35100	23200	1.1
UCX09-27	1-11/16		90	51.6	23	19	32.6	9	6.5	3/8-24UNF	35100	23200	1.01
UCX09-28	1-3/4		90	51.6	23	19	32.6	9	6.5	3/8-24UNF	35100	23200	0.97
UCX09		45	90	51.6	23	19	32.6	9	6.5	M10X1.25	35100	23200	0.95
UCX10-30	1-7/8		100	55.6	25	22.2	33.4	9	7.2	3/8-24UNF	43550	29200	1.43
UCX10-31	1-15/16		100	55.6	25	22.2	33.4	9	7.2	3/8-24UNF	43550	29200	1.32
UCX10		50	100	55.6	25	22.2	33.4	9	7.2	M10X1.25	43550	29200	1.29
UCX10-32	2		100	55.6	25	22.2	33.4	9	7.2	3/8-24UNF	43550	29200	1.26
UCX11-34	2-1/8		110	65.1	27	25.4	39.7	10.5	8.2	3/8-24UNF	47800	32800	1.95
UCX11		55	110	65.1	27	25.4	39.7	10.5	8.2	M10X1.25	47800	32800	1.8
UCX11-35	2-3/16		110	65.1	27	25.4	39.7	10.5	8.2	3/8-24UNF	47800	32800	1.78
UCX11-36	2-1/4		110	65.1	27	25.4	39.7	10.5	8.2	3/8-24UNF	47800	32800	1.7
UCX12		60	120	65.1	28	25.4	39.7	12	8	M12X1.25	57200	40000	2.05
UCX12-38	2-3/8		120	65.1	28	25.4	39.7	12	8	3/8-24UNF	57200	40000	2.03
UCX12-39	2-7/16		120	65.1	28	25.4	39.7	12	8	3/8-24UNF	57200	40000	1.95
UCX13-40	2-1/2		125	74.6	30	30.2	44.4	12	9	7/16-20UNF	60800	45000	2.61
UCX13		65	125	74.6	30	30.2	44.4	12	9	M12X1.25	60800	45000	2.52
UCX14-44	2-3/4		130	77.8	30	33.3	44.5	12	9	7/16-20UNF	66000	49500	2.75
UCX14		70	130	77.8	30	33.3	44.5	12	9	M12X1.25	66000	49500	2.74
UCX15		75	140	82.6	33	33.3	49.3	14	10.3	M12X1.25	71500	54200	3.41
UCX15-48	3		140	82.6	33	33.3	49.3	14	10.3	7/16-20UNF	71500	54200	3.32

UCX16		80	150	85.7	35	34.1	51.6	14	11	M12X1.25	83200	63800	3.87
UCX17-52	3-1/4		160	96	37	39.7	56.3	14	12	7/16-20UNF	95900	71500	4.58
UCX17		85	160	96	37	39.7	56.3	14	12	M12X1.25	95900	71500	5.05
UCX18-56	3-1/2		170	104	39	42.9	61.1	14	12.1	1/2-20UNF	109000	82800	6.12
UCX18		90	170	104	39	42.9	61.1	14	12.1	M14X1.5	109000	82800	6
UCX20		100	190	117.5	44	49.2	68.3	16	13.7	M16X1.5	133000	105000	8.56
UCX20-64	4		190	117.5	44	49.2	68.3	16	13.7	5/8-18UNF	133000	105000	8.33